

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
23 October 2003 (23.10.2003)

PCT

(10) International Publication Number
WO 03/086725 A1

(51) International Patent Classification⁷: **B29B 11/16**,
15/08, B29C 51/00, 51/12, B29D 7/00, C08J 5/04

Shinsa 2-dong, Eunpyeong-gu, Seoul 122-885 (KR). **LEE, Yong-Moo** [KR/KR]; 101-305 Dongbu Haeoreum Apt., Yoksam-dong, Gangnam-gu, Seoul 135-080 (KR).

(21) International Application Number: PCT/KR02/00658

(22) International Filing Date: 11 April 2002 (11.04.2002)

(74) Agent: **KIM, Dong-Kyu**; BYC Building, Suite 501, 648-1, Yoksam 1-dong, Gangnam-gu, Seoul 135-911 (KR).

(25) Filing Language: Korean

(81) Designated States (*national*): AU, BR, CA, CN, DE, GB, HU, ID, IN, JP, KP, NO, NZ, PL, RU, US, VN.

(26) Publication Language: English

(71) Applicant (*for all designated States except US*): **KARAM TECH CO., LTD.** [KR/KR]; 63-2, Busong-ri, Jiksan-myun, Cheonan-shi, Chungcheongnam-do 330-815 (KR).

(84) Designated States (*regional*): Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).

Published:


— with international search report

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **SEO, Duck-Hyun** [KR/KR]; 1105 Samho Park Tower, 1122-10, Ingye-dong, Paldal-gu, Suwon-shi, Gyunggi-do 442-835 (KR). **CHOI, Hyeong-Ki** [KR/KR]; 2-1101 Shinseong Apt., 155-1,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: APPARATUS FOR PROCESSING FIBER-REINFORCED COMPOSITES USING FIBER MAT AND ITS MANUFACTURE



(57) Abstract: Disclosed is a method of manufacturing a multifunctional fiber-reinforced composite using a composite fiber mat and an apparatus for manufacturing the same, in which at least two types of thermoplastic fiber and reinforcing fiber are used to manufacture a composite mat or a composite sheet, as well as a light adiabatic sheet having cells foamed due to inherent resilience of the reinforcing fiber while the composite sheet is compressed by rollers. The method includes fibrillating and combining the thermoplastic fiber and the reinforcing fiber to form the composite mat, dispersing and volatilizing the composite mat, and needle-punching the dispersed and volatilized composite mat. Then, the composite mat is subjected to preheating in a preheating zone, melting, compressing and molding in a compressing zone, and cooling in a cooling zone, to yield the composite sheet. Selectively, the composite sheet is re-heated to obtain a pseudo-foamed composite sheet by inherent resilience of the fiber.

WO 03/086725 A1